made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA An italian tile made in USA

FLORIM USA

STAINED CEMENT

HDG HIGH DEFINITION GRAPHICS

COLOR BODY COLLECTION
MADE WITH HIGH DEFINITION TECHNOLOGY
SIZES AVAILABLE:
8"X48" RECTIFIED
FLOOR / WALL
SHADE VARIATION: V2
THICKNESS: 10MM

COLOR BODY MADE WITH HIGH DEFINITION GRAPHICS
8"x48" Rectified

WHITE

GREY

703122 - SEPTEMBER 2015

FLOOR AND WALL
Tiles with styling and sizes suitable for both floors and walls.

V2

MODERATE VARIATION
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly

Scan this barcode for more care, maintenance, and installation tips at www.florimusa.com

877-Florim1 (356-7461) - www.florimusa.com

FLORIM USA

STAINED CEMENT

HDG HIGH DEFINITION GRAPHICS

COLOR BODY COLLECTION
MADE WITH HIGH DEFINITION TECHNOLOGY
SIZES AVAILABLE:
8”X48” RECTIFIED
FLOOR / WALL
SHADE VARIATION: V2
THICKNESS: 10MM

COLOR BODY MADE WITH HIGH DEFINITION GRAPHICS
8”x48” Rectified

TAUPE

PEARL

703128 - SEPTEMBER 2015

FLOOR AND WALL
Tiles with styling and sizes suitable for both floors and walls.

V2

MODERATE VARIATION
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly

Scan this barcode for more care, maintenance, and installation tips at www.florimusa.com

877-Florim1 (356-7461) - www.florimusa.com

FLORIM USA

STAINED CEMENT

SUGGESTED INSTALLATIONS

PEI Class IV

Moderate to heavy foot traffic

Recommended for all residential applications as well as medium commercial and light institutional applications.

PROGRESS THAT TOUCHES AND INVESTS IN THE ENTIRE SOCIETY
As a active member of the U.S Green Building Council, Florim spreads awareness to the entire American communities and encourages towards the use of building solutions inspired by environmentally friendly practices. Using Florim products for project implementation, will positively contribute in obtaining scores and points required for earning the LEED certification (Leadership in Energy and Environmental Design).

A COMMITMENT TO THE DEVELOPMENT OF PRODUCTS FOR A CONSCIOUS BUILDING TRADE
Florim offers products containing recycled material. The adoption of eco-compatible production systems is merit of Italian designs produced in the U.S.

TECHNICAL DEVELOPMENT THAT CONSIDERS THE NATURAL ENVIRONMENT
Florim commits to the eco-compatible project and translates the same into an avant-guard production process, minimizing the negative impact on the environment.

COLOR BODY MADE WITH HIGH DEFINITION GRAPHICS

8"x48" Rectified

White

Pearl

Taupe

Grey

Grey

V2 MODERATE VARIATION

1096354

Taupe

V2 MODERATE VARIATION

1096355

Pearl

V2 MODERATE VARIATION

1096356

White

V2 MODERATE VARIATION

1096353

MODULAR FIELD TILE

SIZE	WHITE	GREY	TAUPE	PEARL
8"x48" Rectified	1096353	1096354	1096355	1096356

PACKAGING

SIZES	METRIC (CM)	THICKNESS (MM)	PIECES PER BOX	SQ. FT PER BOX	WEIGHT PER BOX	BOXES PER PALLET	WEIGHT PER PALLET
8"x48" Rectified	20x120	10 mm	5	13.33	59.5	42	2,550

ALL OTHER SIZES WILL BE PACKAGED AS ORDERED.
PLEASE CONTACT FLORIM CUSTOMER SERVICE AT 877-FLORIM1 FOR PACKAGING INFORMATION.

✦ MINIMUM GROUT SIZE RECOMMENDED = 5 MM (OR APPROX. 3/16") IF STAGGERED TILE PLACEMENT, WE RECOMMEND USING A 30% OFFSET. IF SPECIFIED BRICK PATTERN WITH 1/2 PATTERN MANDATORY, A BIGGER GROUT IS RECOMMENDED TO HIDE IMPERFECTIONS OF INSTALLATION (MINIMUM 1/4").

TECHNICAL SPECIFICATIONS

Surface Abrasion	PEI	IV	ASTM C1027
Water Absorption		≤ 0.5%	ASTM C373
Chemical Resistance		NOT AFFECTED	ASTM 650
Dynamic Coefficient of Friction		≥ 0.46 •	ANSI 137.1
Stain Resistance		NOT AFFECTED	ASTM C1378
Breaking Strength		≥ 400	ASTM C648
Resistance to Freeze		RESISTANT	ASTM C1026
Scratch Hardness		≥ 6	MOHS

ALL FLORIM USA PRODUCTS MEET OR EXCEED ALL STANDARDS IN ANSI A137.1.
• DUE TO THE INHERENT NATURE OF FIRED PORCELAIN TILE, IT IS IMPORTANT TO NOTE THAT THE COEFFICENT OF FRICTION MAY VARY WITHIN AND BETWEEN PRODUCT RUNS.
*ALL TECHNICAL SPECIFICATIONS ARE FOR FIELD TILE ONLY.

SHADE VARIATION

V1 — UNIFORM APPEARANCE
Differences among pieces from the same production run are minimal.

V2 — SLIGHT VARIATION
Clearly distinguishable differences in texture and/or pattern with similar colors.

V3 — MODERATE VARIATION *
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly.

V4 — SUBSTANTIAL VARIATION *
Random color differences from tile to tile, so that one tile may have totally different colors from that on other tiles. Thus, the final installation will be unique.

* CONSUMERS SHOULD LOOK AT MULTIPLE PIECES OF TILE TO REALIZE THE FULL COLOR SPECTRUM OF THIS PRODUCT

WHY PORCELAIN?

There are many reasons to choose impervious porcelain tile over other floor coverings. It offers the largest array of design options and holds its value the longest.
In a comparison between the many different flooring options, porcelain tile offers one of the most durable and least expensive options over the lifespan of the building.

Benefits of Porcelain Tile

- Impervious to water
- Easy to maintain
- Variety of design options
- Environmentally friendly
- Resistant to germs and bacteria
- Fade resistant
- Fire resistant
- Durable - best long-term value vs. other floor coverings

HOW TO MAINTAIN YOUR PORCELAIN TILE

- Sweep or vacuum regularly.
- Wash with a household cleaner and hot water then rinse with clean water (do not use wax, oil-based, or abrasive cleaners).

Colors Shown in this brochure may vary from actual product.
Final selection should be made from actual product samples.

LEED · Environment PRIORITY ONE · CTDA · TCNA · WE BUILD AMERICAN · 10% RECYCLED CONTENT · Product Certification BUREAU VERITAS Certification

300 International Blvd.
Clarksville, TN 37040
Toll free: 877 - Florim1 (356-7461)
tel. 931 645 5100

www.florimusa.com