








Enjoy the best of both worlds with Galaxy. The essence of sandstone fused with the splendor of porcelain. Galaxy creates a unique tile collection with the appearance and grace of natural stone and the durability and longevity of porcelain tile.










12" x 12" , 12" x 24" / BEIGE









GALAXY / GRIGIO





18" x 18" , 12" x 24" **/ GRIGIO**



GALAXY / NERO





12" x 12" semi-polished / NERO

11.54"x23.19" Rectified Semi-Polished

1095539 Beige

1095540 Silver

1095536 Grigio

1095538 Nero

sizes:

12"x12"

1095533 Beige 1095534 Silver 1095530 Grigio 1095532 Nero

12"x24"

1095568 Beige 1095569 Silver 1095565 Grigio 1095567 Nero

6"x24"

1095562 Beige 1095563 Silver 1095559 Grigio 1095561 Nero

18"x36"

1095578 Beige 1095579 Silver 1095575 Grigio 1095577 Nero

mosaics & trim pieces:

12"x12" Mosaic



1095596 Beige 1095597 Silver 1095593 Grigio 1095595 Nero

3"x12" Bullnose

1095590 Beige 1095591 Silver 1095587 Grigio 1095589 Nero

6"X12" Cove Base *special order only



1095527 Beige 1095528 Silver 1095524 Grigio 1095526 Nero



UNIFORM APPEARANCE
Differences among pieces
from the same production
run are minimal.



Clearly distinguishable differences in texture and/ or pattern with similar colors.



While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly.



SUBSTANTIAL VARIATION Random color differences from tile to tile, so that one tile may have totally different colors from that on other tiles. Thus, the final installation will be unique.





technical specifications

		REFERENCE VALUE	DECLARED VALUE	TEST METHOD		
III	SURFACE ABRASION		IV	ASTM C1027		
	WATER ABSORPTION	≤0.5%	MEETS REQUIREMENT	ASTM C373		
	CHEMICAL RESISTANCE	AS REPORTED	NOT AFFECTED	ASTM 650		
*	DYNAMIC COEFFICIENT OF FRICTION	≥0.42 WET	MEETS REQUIREMENT	ANSI A137.1		
×	STAIN RESISTANCE	AS REPORTED	NOT AFFECTED	ASTM C1378		
۵	BREAKING STRENGTH		≥400	ASTM C648		
*	RESISTANCE TO FREEZE	AS REPORTED	RESISTANT	ASTM C1026		



RESISTANT FOR THE HOUSE The product is water-resistant: it stops liquids, body oils, acidic and staining substances from penetrating the tiles. It resists scratches, scuffs and gauges better than any other floor covering. It does not absorb fumes, odors or smoke. It doesnt discolor or fade when exposed to sunlight, or other natural elements. It is completely fire proof. It resists burns and doesn's feed a fire. Its high resistance to abrasive dirt and grime makes it suitable even for heavy-traffic areas of the house such as hallways, entrances, foyers and walkways.

FROST RESISTANT Exceeding the ADA standard requirements, the Milestone product can also be used for outside applications. It stands up to abrupt temperature changes and freezing-thaw cycles. When properly installed according to ANSI A137.1. It's strong enough to be used in exterior applications even in frigid climates. Proper

consideration must be given to the anti-slip requirements of the area to be tiled.

ANTI-SLIP The testing conducted on our finished product will guarantee that all of our tiles will have an anti-slip surface so they may be used with total confidence in kitchen and bath applications. The Milestone product is perfect for both home and commercial interiors, such as restaurants, offices, retail stores, etc. Its anti-slip properties provide a safe walkking surface in both wet and dry conditions, according to the Americans with

HYGIENE/SANATATION & EASY CLEANING The Milestone product doesn't absorb odors or bacteria of any kind. It's easy to clean with a dampsponge, mop, or cloth. For a more intense cleaning, simply use a mild solution of water and a common household detergent. Regular cleaning will stop the growth of germs and bacteria in damp areas such as the bathroom.

packaging

SIZES	METRIC (CM)	THICKNESS (MM)	PIECES PER BOX		WEIGHT PER BOX	BOXES PER PALLET	UOM PER PALLET	WEIGHT PER PALLET*
FIELD TILES								
12"x12"	30x30	9 mm	14	14	57.4	48	672	2,755
6"x24"	15x60	9 mm	14	14	57.4	48	672	2,755
12"x24"	30x60	9 mm	7	14	57.4	48	672	2,755
11.54"x23.19" RECTIFIED SEMI-POLISHED	30x60	9 mm	7	13	53.4	48	625	2,562
18"x36" RECTIFIED MATTE	45x90	10 mm	3	13.5	59.4	27	364.5	1,604
MOSAICS AND COORDINATING TRIMS								
12"x12" MOSAIC	30x30	10 mm	10	10	41	45	450 pcs	1,845
3"x12" BULLNOSE	7.5x30	10 mm	12	3	12.4	168	216 pcs	2,083
6"x12" COVE BASE	15x30	7 mm	10	5	17.5	64	640 pcs	1,120

^{*} WEIGHT PER PALLET DOES NOT INCLUDE PALLET WEIGHT ITSELF.
ALL OTHER SIZES WILL BE PACKAGED AS ORDERED.
PLEASE CONTACT MILESTONE CUSTOMER SERVICE AT 1-877-356-7461 FOR PACKAGING INFORMATION.

MINIMUM GROUT SIZE RECOMMENDED = 5 MM (OR APPROX. 3/16") IF STAGGERED TILE PLACEMENT, WE RECOMMEND USING A 30% OFFSET. IF SPECIFIED BRICK PATTERN WITH 1/2 PATTERN MANDATORY, A BIGGER GROUT IS RECOMMENDED TO HIDE IMPERFECTIONS OF INSTALLATION (MINIMUM 1/4").

[•] DUE TO THE INHERENT NATURE OF FIRED PORCELAIN TILE, IT IS IMPORTANT TO NOTE THAT THE COEFFICENT OF FRICTION MAY VARY WITHIN AND BETWEEN PRODUCT RUNS.

Routine care instructions:

Wash with water to remove superficial dirt.
 Application of Fila Cleaner® Fila (commercial product) diluted to an average of 1:200 to the surface.
 Let the solution sit 5-7 minutes.

4. Remove the cleaner with a vigorous mechanical cleaning action using common hand cleaning equipment, or a suitable floor-cleaning appliance.

5. Dry the floor completely.

Note: For desired results, it is particularly important to combine the effect of the detergent with a vigorous mechanical cleaning action.

The products mentioned in these instructions do not officiate any official agreements with any floor cleaning product producers.





Contributes

to LEED credits

CERTIFICATIONS

PROGRESS THAT TOUCHES AND INVESTS IN THE ENTIRE SOCIETY

As a active member of the U.S Green Building Council, Milestone spreads awareness to the entire American communities and encourages towards the use of building solutions inspired by environmentally friendly practices. Using Milestone products for project implementation, will positively contribute in obtaining scores and points required for earning the LEED certification

(Leadership in Energy and Environmental Design).

A COMMITMENT TO THE DEVELOPMENT OF PRODUCTS FOR A CONSCIOUS BUILDING TRADE

Milestone offers products containing recycled material. The adoption of eco-compatible production systems is merit of Italian designs produced in the U.S.

TECHNICAL DEVELOPMENT THAT CONSIDERS THE NATURAL ENVIRONMENT

Milestone commits to the eco-compatible project and translates the same into an avant-guard production process, minimizing the negative impact on the environment.

WHY PORCELAIN?

There are many reasons to choose impervious porcelain tile over other floor coverings. It offers the largest array of design options and holds its value the longest. In a comparison between the many different flooring options, porcelain tile offers one of the most durable and least expensive options over the lifespan of the building.

Benefits of Porcelain Tile

- Impervious to water
- Easy to maintain
- Variety of design options
- Environmentally friendly
- · Resistant to germs and bacteria
- Fade resistant
- Fire resistant
- Durable best long-term value vs. other floor coverings

SUGGESTED INSTALLATIONS

PEI Class

Moderate to heavy foot traffic

Recommended for all residential applications as well as medium commercia and light institutional applications.



300 International Blvd. Clarksville, TN 37040 | www.milestonetiles.com | 1-877-356-7461

